



## 25ym Honda CRF125F

### General

Warranty	-
Service Intervals	As per User Manual

### Dimensions & Weights

Claimed KERB Weight (kg)	90.27 kg
Length (mm)	1 857 mm
Width (mm)	769 mm
Height (mm)	1 069 mm
Seat Height (mm)	785 mm
Wheel Base (mm)	1 255 mm
Trail (mm)	94 mm
Caster Angle (degrees)	27°30'
Ground Clearance (mm)	267 mm

### Suspension

Type Front	Inverted telescopic fork. 16.8cm of travel
Type Rear	Single shock. 16.8cm of travel

### Engine

Type	Air cooled, two valve, four stroke SOHC 25° single cylinder
Displacement	124.9cc
Bore x Stroke (mm)	52.4.0 mm x 57.9 mm
Compression Ratio	9.0:1
Carburation	Fuel injection
Fuel Tank Capacity	4.5L (inc. reserve)
Starter	Electric and kickstarter

### Drive Train

Clutch Type	Wet multiplate
Transmission Type	Manual 4-speed
Final Drive	Chain 13T/49Tt

### Safety

Front Brakes	Hydraulic, single 220mm disc
Rear Brakes	Drum

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



## 25ym Honda CRF125F

### Frame

Type Steel

### Wheels

Type Front Aluminium spoke

Type Rear Aluminium spoke

Tyres Front 10/100-19 w/tube

Tyres Rear 90/100-16 w/tube

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.