

**NC750X****Honda NC750XA | Honda NC750XD (DCT)****General**

Warranty	2 yrs
Service Intervals	12 000kms

Dimensions & Weights

	NC750X A	NC750X D
Claimed KERB Weight (kg)	216 kgs	226 kgs
Length (mm)	2 210 mm	2 210 mm
Width (mm)	846 mm	846 mm
Height (mm)	1 330 mm	1 330 mm
Seat Height (mm)	802 mm	802 mm
Wheel Base (mm)	1 525 mm	1 530 mm
Trail (mm)	110 mm	110 mm
Caster Angle (degrees)	27°	27°
Ground Clearance (mm)	145 mm	145 mm
Turning radius (m)	3 m	3 m

Battery

Battery Type	AGM
Battery Capacity	12 V 11 Ah(10HR) / 11.6 Ah(20HR)

Engine

	NC750X A	NC750X D
Tank Capacity (l)	14,1l	14,1l
Fuel System	PGM-FI	PGM-FI
Starter	E-Starter	E-Starter
Fuel Consumption	3.5 L/100km	3.5 L/100km
Engine Configuration	Liquid-cooled, four stroke, eight valve SOHC Parallel Twin	
Displacement (cm ³)	745cc	745cc
Max Speed	173 km/h	170 km/h
Stationary sound level - dB (A)	88 dB (A)	88 dB (A)
Bore x Stroke (mm)	77mm x 80mm	
Compression Ratio	10,7:1	10,7:1
Power (kW)	43.1kW / 6 750 RPM	
Torque (Nm)	69Nm / 4 750 RPM	
Oil Capacity (l)	4l	4l

Safety

ABS System Type	Dual Channel ABS
Front Brakes	Axial mounted twin-piston brake caliper, 296 mm floating double disc
Rear Brakes	Single piston caliper, 240 mm single disc

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

**NC750X****Honda NC750XA | Honda NC750XD (DCT)****Drive Train**

	NC750XA	NC750XD
Final Drive	Chain	Chain
Clutch Type	Wet Multiple Clutch	2x Wet Multiplate Clutch
Transmission Type	6-speed Manual Transmission	6-speed Dual Clutch Transmission

Suspension

Front Suspension	41mm telescopic fork, 120mm Stroke
Rear Suspension	Monoshock damper, Pro-Link swingarm, 120mm travel

Wheels

Wheels Front	17M/C X MT3.50 Multi-spoke cast aluminium
Wheels Rear	17M/C X MT4.50 Multi-spoke cast aluminium
Tyres Front	120/70ZR17 M/C
Tyres Rear	160/60ZR17 M/C

Styling

Frame Type	Diamond Steel Pipe Frame
------------	--------------------------

Instruments & Electronics

Instruments	5-inch TFT Screen
Headlight	LED
Taillight	LED
Connectivity	RoadSync
USB	Optional (Type-C)
Security System	HISS
Riding mode	Standard, Sport, Rain, User 1 and User 2
HSTC	3 Level + OFF

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

