



**True
Adventure**

24ym Honda CRF1100A2/D4 Adventure Sport

General

Warranty	2 yrs
Service Intervals	12 000kms

Dimensions & Weights

	Manual	DCT
Claimed KERB Weight (kg)	243 kgs	253 kgs
Dimensions (LxWxH)	2,305mm X 960mm X 1,475mm	
Wheelbase	1,570mm	
Caster Angle	27.5°	
Trail	106mm	
Seat Height	835/855mm (low seat option 795mm)	
Ground Clearance (mm)	220mm	
Turning radius (m)	2.6m	

Wheels

Tyres (f)	110/80-R19M/C 59V (Tubeless type) Bridgestone Battlax Adventure A41
Tyres (r)	150/70-R18M/C 70H (Tubeless type) Bridgestone Battlax Adventure A41
Wheels (f)	19M/C x MT2.50 wire spoke with aluminium rim
Wheels (r)	18M/C x MT4.00 wire spoke with aluminium rim

Engine

	Manual	DCT
Oil Capacity (l)	4,8l	5,2l
Type	Liquid-cooled OHC 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam	
Displacement (cm ³)	1084cc	
Bore x Stroke (mm)	92mm x 81.5mm	
Compression Ratio	10.5:1	
Max Power (kW)	75kW @ 7,500rpm	
Torque (Nm)	112Nm @ 5,500rpm	
Carburation	PGM-FI	
Fuel Tank Capacity (l)	24.8l	
CO ² Emissions	114g/km	
Fuel Consumption	20.5km/l (4.9 l/100km)	
Noise Level	Lurban 75.0dB, Lwot 80.5dB	Lurban 75.4dB, Lwot 80.4dB

Drive Train

	Manual	DCT
Drive	O-ring Sealed Chain	O-ring Sealed Chain
Transmission Type	6-speed manual	6-speed DCT
Clutch Type	Wet, multiplate with coil springs, Aluminium Cam Assist and Slipper clutch	2 wet, multiplate clutches with coil springs

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



**True
Adventure**

24ym Honda CRF1100A2/D4 Adventure Sport

Suspension

Front Suspension	SHOWA Telescopic inverted fork with an inner tube diameter of 45mm, and an electronic control unit (SHOWA EERATM) with compression and rebound damping adjustments, 210mm stroke
Rear Suspension	Monoblock aluminium swing arm with Pro-Link with SHOWA gas-charged damper, hydraulic remote control preload adjuster and electronic control unit (SHOWA EERATM) with compression and rebound damping adjustments, 200 mm rear wheel travel.

Safety

ABS System Type	2 channel with IMU Selectable ABS MODE with ON road and OFF road setting
Front Brakes	310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers and sintered metal pads
Rear Brakes	256mm wave hydraulic disc with 2-piston caliper and sintered metal pads. 2-channel with rear ABS off mode.

Styling

Frame Material	Semi Double Cradle
----------------	--------------------

Instruments & Electronics

Instruments	LCD Meter, TFT 6.5inch touch panel multi information display
Headlight	LED
Taillight	LED
Connectivity	Bluetooth and Apple CarPlay®/Android Auto® (wired)
USB	Yes
12V Socket	Yes
Auto Winker Cancel	Yes
Quickshifter	Optional (MT only)
Security System	Immobiliser
Cruise Control	Yes
Cornering Lights	Yes
Additional Features	Emergency stop signal, 6 axis IMU, HSTC and Wheelie control
Riding Modes	Tour, Urban, Gravel, Off-Road, 2 x User Modes

Electrical System

Starter	Electric
Battery Capacity	12V-6Ah Li-ion BATTERY

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.