



Honda CRF450X

General

Service Intervals As Per User Manual

Dimensions & Weights

Claimed KERB Weight (kg)	124.74 (Ready to Ride)
Seat Height (mm)	963 mm
Wheel Base (mm)	1 491 mm
Ground Clearance (mm)	332 mm
Caster Angle (degrees)	27.6
Trail (mm)	142 mm

Drive Train

Drive	#520 Chain; 13T/51T
Gearbox	Wide-Ratio, 6-speed
Front Suspension	49mm Leading Axle inverted Showa® fork; 305mm travel
Rear Suspension	Pro-Link® Showa® single shock; 300mm travel

Instruments & Electronics

Headlight	Halogen
Taillight	LED

Engine

Tank Capacity (l)	7.6l
Fuel System	PGM-FI, 46mm downdraft throttle body
Starter	Electric
Engine Configuration	449cc liquid-cooled, single-cylinder four-stroke
Cylinders	1
Valves Per Cylinder	4
Valve Train	Unicam® SOHC
Bore x Stroke (mm)	96 x 62.1
Compression Ratio	12,1:1

Wheels

Tyres (f)	Dunlop, MX52 80/100-21
Tyres (r)	Dunlop, MX52 110/100-18
Rim Size (f)	21"
Rim Size (r)	18"

Safety

Front Brakes	Single 260mm disc with twin-piston caliper
Rear Brakes	Single 240mm disc

Styling

Frame Material	Aluminium Twin Spar Chassis
----------------	-----------------------------

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.