



## 26ym Honda TRX250TM

### General

Warranty	Transferable, (6 Month) included, limited warranty
Service Intervals	As per User Manual

### Dimensions & Weights

Claimed KERB Weight (kg)	201 kg
Length (mm)	1 905 mm
Width (mm)	1 033.80 mm
Height (mm)	1 069 mm
Seat Height (mm)	792.50 mm
Wheel Base (mm)	1 130 mm
Ground Clearance (mm)	152.60 mm
Towing Capacity	227 kgs
Front Rack Capacity	15 kg
Rear Rack Capacity	30 kg
Turning Radius (m)	2.6 m
Fuel Capacity	9.1 Ltr.

### Suspension

Front Suspension	Independent double-wishbone; 130mm travel
Rear Suspension	Swingarm with single shock; 125mm travel

### Engine

Type	229cc air-cooled longitudinally mounted single-cylinder four-stroke
Valve Train	OHV; two valves per cylinder
Bore x Stroke (mm)	68.5 mm x 62.2 mm
Compression Ratio	9.2:1
Induction	22mm piston-valve carburetor
Starter	Electric with optional auxiliary recoil
Transmission	Five-speed ATV-style semi-automatic with reverse
Driveline	Direct rear driveshaft

### Safety

Front Brakes	Dual 130mm drums
Rear Brakes	140mm drum

### Wheels

Tyres Front	22 x 7-11
Tyres Rear	22 x 10-9

### Other

Emissions	Meets current EPA off-road emissions standards.
Model ID	TRX250TE
important Safety Information	Recommended for riders 16 years of age and older. Honda recommends that all ATV riders take a training course and read their owner's manual thoroughly.



All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.