



Business Ready,
RIDER APPROVED!





ELITE125



ACE125



ACE150



XR125L

| CATEGORY | SCOOTER | COMMERCIAL |
|--------------------------------------|-----------------------------------------------------------------------|--------------------------------------------------------------|
| DIMENSIONS & WEIGHTS | | |
| Claimed KERB Weight (kg) | 109 | 110 |
| Dimensions LxHxW (mm) | 1785 x 694 x 1139 | 2050 x 751 x 1059 |
| Seat Height (mm) | 749 | 790 |
| Wheel Base (mm) | 1234 | 1310 |
| Caster Angle | - | - |
| Trail (mm) | - | - |
| Ground Clearance (mm) | - | - |
| DRIVE | | |
| Drive | V-Belt | Chain |
| Suspension Front / Rear | Telescopic Forks, 80mm Axle Travell / Unit Swingarm, 64mm Axle Travel | 31mm Telescopic forks, 130mm Axle Travel / Pro-Link Swingarm |
| ENGINE | | |
| Type | Air-cooled, 4-Stroke, OHC 2 valve Single Cylinder | Air-cooled, Single Cylinder |
| Displacement (cc) | 124,6 | 124,1 |
| Bore / Stroke (mm) | - | - |
| Compression Ratio | - | - |
| Fuel Consumption | - | - |
| Power (KW) | 6.25 kW / 8,000 rpm | 6.32 kW / 6,500 rpm |
| Torque (NM) | 9.25 Nm / 6,500 rpm | 10.12 Nm / 5,000 rpm |
| Air Filter Type | - | - |
| Tank Capacity (l) | 6 | 10 |
| Starter | Electric | Kick & Electric |
| Fuel System | CV Carburetor | Carburetor |
| Cylinders | 1 | 1 |
| Valves Per Cylinder | 2 | 2 |
| Gearbox | V - Matic | 4-speed |
| SAFETY | | |
| Brakes Front / Rear | Single Disc / Drum *with combined braking system | 130mm Leading/Trailing Drum |
| STYLING | | |
| Frame Material | Underbone, Steel Tube | Diamond, Steel |
| WHEELS | | |
| Tyres Front / Rear | 90/90 - 12 / 100/90 - 10 | 80/100-18 / 90/90-18 |
| Wheels | 5 Spoke cast aluminium | Alloy |
| INSTRUMENTS & ELECTRONICS | | |
| USB Socket | - | - |
| Speedometer / Fuel Gauge | - | - |
| Gear Indicator | - | - |
| Headlight | Halogen | Halogen |
| Taillight | Halogen | Halogen |

| STREET | COMMERCIAL / DUAL PURPOSE |
|----------------------------------------------------------------------------------------|------------------------------------------------------------------|
| 125 | 128 |
| 2050 x 751 x 1160 | 2091 x 811 x 1125 |
| 790 | 825 |
| 1310 | 1358 |
| 27° 17" | - |
| 98 | - |
| 165 | 243 |
| Chain | Chain |
| Telescopic Fork, 116mm Axle Travel Leading/Trailing Drum / Swing Arm, 91mm Axle Travel | 31mm Telescopic Fork, 160mm Axle Travel / Swing-Arm 151mm Travel |
| Air-cooled, 4-Stroke 2-Valve OHC Single Cylinder | Air-cooled 4-Stroke 2-valve OHV single |
| 150 | 124,1 |
| 57.3 / 57.9 | - |
| 9.5:1 | - |
| 49Km/L | - |
| 8.74 kW / 7,500 rpm | - |
| 11.99 Nm / 5,500 rpm | - |
| Oiled Polyurethane Foam | - |
| 11,8 | 12 |
| Kick & Electric | Kick & Electric |
| Carburettor | Carburetor |
| 1 | 1 |
| 2 | 2 |
| 5-Speed | 5-speed |
| Leading/Trailing Drum | 240mm Hydraulic Disk / 110mm Leading/Trailing Drum |
| Diamond, Steel | Steel, Semi-Double Cradle |
| 80/100-18M/C 47P / 90/90-18M/C 51P | 90/90-19 / 110/90-17 |
| Alloy | Wire Spoke Wheel |
| 12W (5V, 2.4 A) | - |
| • / • | - |
| Digital | - |
| Halogen | Halogen |
| Halogen | Halogen |



AFTER SALES

Warranty: 2 Years / Unlimited Km

Service Intervals: 4000 Km

www.honda.co.za

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.