



www.honda.co.za

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



Business Ready, RIDER APPROVED



2 Year / Unlimited km Warranty



ACTIVA125

ACE125

ACE150

XR125L

CATEGORY	SCOOTER	COMMERCIAL
AFTER SALES		
Warranty	2 Year / Unlimited km	2 Year / Unlimited km
Service Intervals	6000km	4000km
DIMENSIONS & WEIGHTS		
Claimed KERB Weight (kg)	106	110
Dimensions LxHxW (mm)	1850 x 707 x 1170	2050 x 751 x 1059
Seat Height (mm)	765	790
Wheel Base (mm)	-	1310
Caster Angle	-	-
Trail (mm)	-	-
Ground Clearance (mm)	162	-
DRIVE		
Drive	-	Chain
Suspension Front / Rear	Telescopic Fork (Non-Adjustable) / 3-step Adjustable Spring-loaded Hydraulic Unit	31mm Telescopic forks, 130mm Axle Travel / Pro-Link Swingarm
ENGINE		
Type	1-Cylinder, 4-stroke, Air-cooled, SOHC 2-valve	Air-cooled, Single Cylinder
Displacement (cc)	124	124,1
Bore / Stroke (mm)	-	-
Compression Ratio	-	-
Fuel Consumption	-	-
Power (KW)	6.11 kW / 6,250 rpm	6.32 kW / 6,500 rpm
Torque (NM)	10.4 Nm / 5,000 rpm	10.12 Nm / 5,000 rpm
Air Filter Type	-	-
Tank Capacity (l)	5.3	10
Starter	Electric	Kick & Electric
Fuel System	Fuel Injection	Carburetor
Cylinders	1	1
Valves Per Cylinder	2	2
Gearbox	-	4-speed
SAFETY		
Brakes Front / Rear	Single Disc / Drum *with combined braking system	130mm Leading/Trailing Drum
STYLING		
Frame Material	-	Diamond, Steel
WHEELS		
Tyres Front / Rear	-	80/100-18 / 90/90-18
Wheels	-	Alloy
INSTRUMENTS & ELECTRONICS		
USB Socket	-	-
Speedometer / Fuel Gauge	-	-
Gear Indicator	-	-
Headlight	LED	Halogen
Taillight	LED	Halogen

	STREET	COMMERCIAL / DUAL PURPOSE
AFTER SALES		
Warranty	2 Year / Unlimited km	2 Year / Unlimited km
Service Intervals	4000km	4000km
DIMENSIONS & WEIGHTS		
Claimed KERB Weight (kg)	125	128
Dimensions LxHxW (mm)	2050 x 751 x 1160	2091 x 811 x 1125
Seat Height (mm)	790	825
Wheel Base (mm)	1310	1358
Caster Angle	27° 17"	-
Trail (mm)	98	-
Ground Clearance (mm)	165	243
DRIVE		
Drive	Chain	Chain
Suspension Front / Rear	Telescopic Fork, 116mm Axle Travel Leading/Trailing Drum / Swing Arm, 91mm Axle Travel	31mm Telescopic Fork, 160mm Axle Travel / Swing-Arm 151mm Travel
ENGINE		
Type	Air-cooled, 4-Stroke 2-Valve OHC Single Cylinder	Air-cooled 4-Stroke 2-valve OHV single
Displacement (cc)	150	124,1
Bore / Stroke (mm)	57.3 / 57.9	-
Compression Ratio	9.5:1	-
Fuel Consumption	49Km/L	-
Power (KW)	8.74 kW / 7,500 rpm	-
Torque (NM)	11.99 Nm / 5,500 rpm	-
Air Filter Type	Oiled Polyurethane Foam	-
Tank Capacity (l)	11,8	12
Starter	Kick & Electric	Kick & Electric
Fuel System	Carburetor	Carburetor
Cylinders	1	1
Valves Per Cylinder	2	2
Gearbox	5-Speed	5-speed
SAFETY		
Brakes Front / Rear	Leading/Trailing Drum	240mm Hydraulic Disk / 110mm Leading/Trailing Drum
STYLING		
Frame Material	Diamond, Steel	Steel, Semi-Double Cradle
WHEELS		
Tyres Front / Rear	80/100-18M/C 47P / 90/90-18M/C 51P	90/90-19 / 110/90-17
Wheels	Alloy	Wire Spoke Wheel
INSTRUMENTS & ELECTRONICS		
USB Socket	12W (5V, 2.4 A)	-
Speedometer / Fuel Gauge	• / •	-
Gear Indicator	Digital	-
Headlight	Halogen	Halogen
Taillight	Halogen	Halogen