



Honda CRF1100A/D Africa Twin

General

Warranty	2 yrs
Service Intervals	12 000kms

Dimensions & Weights

	Manual	DCT
Claimed KERB Weight (kg)	231 kgs	242 kgs
Dimensions (LxWxH)	2,330mm x 960mm x 1,485mm	
Wheelbase	1,575mm	
Caster Angle	27.5°	
Trail	113mm	
Seat Height	850/870mm (Low Seat option 825, Comfort Seat option 885)	
Ground Clearance (mm)	250mm	

Suspension

Front Suspension	Showa 45mm cartridge-type inverted telescopic fork with dial-style preload adjuster and DF adjustments, 230mm stroke.
Rear Suspension	Monoblock aluminium swing arm with Pro-Link with SHOWA gas-charged damper, hydraulic dial-style preload adjuster and rebound damping adjustments, 220 mm rear wheel travel.

Engine

	Manual	DCT
Oil Capacity (l)	4,8l	5,2l
Type	Liquid-cooled OHC 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam	
Displacement (cm ³)	1084cc	
Bore x Stroke (mm)	92mm x 81.5mm	
Compression Ratio	10.5:1	
Max Power (kW)	75kW @ 7,500rpm	
Torque (Nm)	112Nm @ 5,500rpm	
Carburation	PGM-FI	
Fuel Tank Capacity (l)	18.8l	
CO ² Emissions	114g/km	
Fuel Consumption	20.5km/l (4.9 l/100km)	
Noise Level	Lurban 75.1dB, Lwot 80.1dB	Lurban 75.0dB, Lwot 79.9dB

Electrical System

Starter	Electric
Battery Capacity	12V-6Ah Li-ion BATTERY (20Hr)

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



Honda CRF1100A/D Africa Twin

Drive Train

	<i>Manual</i>	<i>DCT</i>
Drive	O-ring Sealed Chain	O-ring Sealed Chain
Transmission Type	6-speed manual	6-speed DCT
Clutch Type	Wet, multiplate with coil springs, Aluminium Cam Assist and Slipper clutch	2 wet, multiplate clutches with coil springs

Safety

ABS System Type	2 channel with IMU Selectable ABS MODE with ON road and OFF road setting
Front Brakes	310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers and sintered metal pads
Rear Brakes	256mm wave hydraulic disc with single piston caliper and sintered metal pads.

Wheels

Tyres (f)	90/90-21M/C 54H (tubeless type) Metzler Karoo Street)
Tyres (r)	150/70R18M/C 70H (tubeless type) Metzler Karoo Street)
Wheels (f)	21M/C x MT2.15 wire spoke with aluminium rim
Wheels (r)	18M/C x MT4.00 wire spoke with aluminium rim

Instruments & Electronics

Instruments	LCD Meter, TFT 6.5inch touch panel multi information display
Headlight	LED
Taillight	LED
Connectivity	Bluetooth and Apple CarPlay®/Android Auto® (wired)
USB	Yes
12V Socket	Yes
Auto Winker Cancel	Yes
Quickshifter	Optional (MT only)
Security System	Immobiliser
Cruise Control	Yes
Cornering Lights	No
Additional Features	Emergency stop signal, 6 axis IMU, HSTC and Wheelie control
Riding Modes	Tour, Urban, Gravel, Off-Road, 2 x User Modes

Styling

Frame Material	Semi Double Cradle
----------------	--------------------

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.