



25ym Honda CRF110F

General

Warranty	-
Service Intervals	As per User Manual

Dimensions & Weights

Claimed KERB Weight (kg)	76.66 kg
Length (mm)	1 541 mm
Width (mm)	678 mm
Height (mm)	922 mm
Seat Height (mm)	657 mm
Wheel Base (mm)	1 064mm
Trail (mm)	53 mm
Caster Angle (degrees)	25°10'
Ground Clearance (mm)	170 mm

Suspension

Type Front	Conventional telescopic fork. 9.9cm of travel
Type Rear	Single shock. 9.65cm of travel

Engine

Type	Air cooled, two valve, four stroke SOHC 80° single cylinder
Displacement	109.2 cc
Bore x Stroke (mm)	50.0 mm x 55.6 mm
Compression Ratio	9.0:1
Carburation	Fuel injection
Fuel Tank Capacity	4.5L (inc. reserve)
Starter	Electric and kickstarter

Drive Train

Clutch Type	Automatic
Transmission Type	Manual 4-speed
Final Drive	Chain

Safety

Front Brakes	Drum
Rear Brakes	Drum

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



25ym Honda CRF110F

Frame

Type

Steel

Wheels

Type Front

Aluminium spoke

Type Rear

Aluminium spoke

Tyres Front

70/100-14 w/tube

Tyres Rear

80/100-12 w/tube

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.