

## General

Warranty
Service Intervals
As per User Manual

# **Dimensions & Weights**

Claimed KERB Weight (kg)	102kg (107kg w <mark>et)</mark>
Length (mm)	2 179 mm
Width (mm)	827 mm
Height (mm)	1 262 mm
Seat Height (mm)	955mm
Wheel Base (mm)	1 483mm
Trail (mm)	117mm
Caster Angle (degrees)	28°24′
Ground Clearance (mm)	330mm

# Suspension

Type Front	49mm Showa coil-spring USD fork. 310mm stroke
Type Rear	Showa Mono shock with Honda Pro-Link 308mm
	axle travel

# **Engine**

Туре	Liquid-cooled 4-stroke single cylinder DOHC
Displacement	249.4cc
Bore x Stroke (mm)	79mm x 50.9mm
Compression Ratio	13.9:1
Oil Capacity	1.251
Carburation	Fuel injection
Fuel Tank Capacity	6.31
Starter	Electric

# **Drive Train**

Clutch Type	Wet multiplate
Transmission Type	Constant mesh
Final Drive	Chain

## Safety

Front Brakes	260mm hydraulic wave disc	
Rear Brakes	240mm hydraulic wave disc	







#### Frame

Type Aluminium twin tube

## Wheels

Type Front	21 x 1.6in Aluminium spoke ni <mark>pple</mark>
Type Rear	19 x 1.85 Aluminium spoke nip <mark>ple</mark>
Tyres Front	80/100-21 PIRELLI MX32 MIDSOFT(CRF250R)
Tyres Rear	100/90-19 PIRELLI MX32 MIDSOFT(CRF250R)

## **Additional Features**

Electronics	3 x HRC Launch Control Modes
Electronics	3 Level HSTC (Honda selectable torque control)
Electronics	3 x Mapping Mode EMSB (Engine mode select button)

