



Honda CRF300L | Honda CRF300 Rally

General

Warranty	2 yrs
Service Intervals	12 000kms

Dimensions & Weights

	CRF300L	CRF300 Rally
Claimed KERB Weight (kg)	142 kgs	153 kgs
Length (mm)	2 230 mm	2 230 mm
Width (mm)	820 mm	920 mm
Height (mm)	1 200 mm	1 415 mm
Seat Height (mm)	880 mm	885 mm
Wheel Base (mm)	1 455 mm	1 455 mm
Trail (mm)	109 mm	109 mm
Caster Angle (degrees)	27.5°	27,5
Ground Clearance (mm)	285 mm	275 mm
Turning Radius (m)	2,3 m	2,3 m

Drive Train

Clutch Type	Wet multiplate, Assisted slipper clutch
Transmission Type	6-speed Manual Transmission
Final Drive	Chain

Engine

	CRF300L	CRF300 Rally
Tank Capacity (l)	7,8l	12,8l
Fuel System	PGM-FI	PGM-FI
Starter	E-Starter	E-Starter
Fuel Consumption	3.1 L/100km	3.1 L/100km
Engine Configuration	Liquid-cooled, Single, DOHC	
Displacement (cm ³)	286cc	286cc
Noise Level (dB)	86 dB	86 dB
Bore x Stroke (mm)	76,0mm x 63,0mm	
Compression Ratio	10,7:1	10,7:1
Power (kW)	20.1kW at 8500rpm	
Torque (Nm)	26.6Nm at 6500rpm	
Max Speed	132 km/h	135 km/h
Oil Capacity (l)	1,8l	1,8l

Suspension

Front Suspension	43 mm Telescopic USD forks 234 mm travel (Suspension stroke 260mm)
Rear Suspension	Pro-Link 260 mm travel

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



Honda CRF300L | Honda CRF300 Rally

Safety

	<i>CRF300L</i>	<i>CRF300 Rally</i>
ABS System Type	2 Channel ABS	2 Channel ABS
Front Brakes	Dual-piston brake caliper, 256 mm floating double disc	Dual-piston brake caliper, 296 mm floating double disc
Rear Brakes	Mono-piston caliper, 220 mm single disc	Mono-piston caliper, 220 mm single disc

Wheels

Wheel Front	Aluminium Rim / spoke
Wheel Rear	Aluminium Rim / spoke
Tyres Front	80/100-21M/C 51P
Tyres Rear	120/80-18M/C 62P

Instruments & Electronics

	<i>CRF300L</i>	<i>CRF300 Rally</i>
Instruments	LCD	LCD
Headlight	LED	LED
DLR	Yes	Yes
Taillight	Bulb	Bulb

Styling

Frame Type	Steel semi-double cradle
------------	--------------------------

Battery

Battery Type	AGM
Battery Capacity	12 V 7 Ah