



## Honda Elite 125

### General

Warranty	2 yrs / Unlimited Km
Service Intervals	4 000kms

### Dimensions & Weights

Claimed KERB Weight (kg)	109 kgs
Length (mm)	1 785 mm
Width (mm)	694 mm
Height (mm)	1 139 mm
Seat Height (mm)	749 mm
Wheel Base (mm)	1 234 mm
Storage	Under Seat Compartment

### Drive Train

Drive	V-Belt
Transmission Type	V - Matic
Front Suspension	Telescopic forks, 80mm axle travel
Rear Suspension	Unit Swingarm, 64mm axle travel

### Wheels

Tyres (f)	90/90 - 12
Tyres (r)	100/90 - 10
Wheels	5 Spoke cast aluminium

### Engine

Tank Capacity (l)	6l
Fuel System	CV Carburetor
Starter	Electric
Engine Configuration	Air Cooled, 4 - Stroke, OHC 2 valve single cylinder
Displacement (cm <sup>3</sup> )	124,6cc
Cylinders	1
Valves Per Cylinder	2
Power (kW)	6.25kW / 8,000 RPM
Torque (Nm)	9.25Nm / 6,500 RPM

### Safety

Brakes	(f) Single Disc (r) Drum With combined braking system.
--------	---

### Instruments & Electronics

Instruments	Standard
Headlight	Halogen
Taillight	Halogen

### Styling

Frame Material	Underbone, steel tube
----------------	-----------------------

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.