



NC750X

Honda NC750XA | Honda NC750XD (DCT)

General

Warranty	2 yrs
Service Intervals	12 000kms

Dimensions & Weights

	NC750XA	NC750XD
Claimed KERB Weight (kg)	214 kgs	224 kgs
Length (mm)	2 210 mm	2 210 mm
Width (mm)	846 mm	846 mm
Height (mm)	1 330 mm	1 330 mm
Seat Height (mm)	800 mm	800 mm
Wheel Base (mm)	1 535 mm	1 535 mm
Trail (mm)	110 mm	110 mm
Caster Angle (degrees)	27	27
Ground Clearance (mm)	145 mm	145 mm

Safety

ABS System Type	2 Channel ABS
Front Brakes	320mm single wavy hydraulic disc with 2-piston calipers & sintered metal pads
Rear Brakes	240mm single wavy hydraulic disc with single-piston caliper & resin mold pads

Engine

	NC750XA	NC750XD
Tank Capacity (l)	14,1l	14,1l
Fuel System	PGM-FI	PGM-FI
Starter	Electric	Electric
Fuel Consumption	28,3km/l	28,3km/l
Engine Configuration	Liquid-cooled 4-stroke 8-valve, SOHC parallel 2-cylinder. EURO5 compliant	
Displacement (cm ³)	745cc	745cc
Cylinders	2	2
Valves Per Cylinder	4	4
Bore x Stroke (mm)	77mm x 80mm	
Compression Ratio	10,7:1	10,7:1
Power (kW)	43.1kW / 6 750 RPM	
Torque (Nm)	69Nm / 4 750 RPM	
Oil Capacity (l)	4l	4l
Battery Capacity	12V/11AH	12V/11AH

Suspension

Front Suspension	41mm telescopic fork, 120mm Stroke
Rear Suspension	Monoshock damper, Pro-Link swingarm, 120mm travel

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



**NC750X****Honda NC750XA | Honda NC750XD (DCT)****Drive Train**

	<i>NC750XA</i>	<i>NC750XD</i>
Drive	Chain	Chain
Clutch Type	Wet Multiple Clutch	Wet Multiple Hydraulic 2-clutch
Gearbox	6-speed Manual	6-speed Dual Clutch

Wheels

Tyres (f)	120/70-ZR17 M/C (58W)
Tyres (r)	160/60-ZR17 M/C (69W)
Rim Size (f)	17M/C x MT3.50
Rim Size (r)	17M/C x MT4.50
Wheels	Multi-Spoke Cast Aluminium

Styling

Frame Material	Diamond; steel pipe
----------------	---------------------

Instruments & Electronics

Security System	HISS
Headlight	LED
Taillight	LED
Instruments	Digital speedometer Digital bar-type tachometer Clock Bar-type fuel meter Two trip meters Gear position indicator 'Instant' and 'Average' fuel consumption Coolant temperature warning light.

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

