

**NX**
500**Honda NX500**

General

Warranty	2 yrs / Unlimited Km
Service Intervals	12 000kms

Dimensions & Weights

Claimed KERB Weight (kg)	196 kgs
Length (mm)	2 165 mm
Width (mm)	830 mm
Height (mm)	1 415 mm
Seat Height (mm)	830 mm
Wheel Base (mm)	1 445 mm
Ground Clearance (mm)	180 mm
Turning Radius (m)	2,4 m
Caster Angle (degrees)	27,5

Suspension

Front Suspension	Showa 41mm SFF-BP USD Forks
Rear Suspension	Pro Link Mono with 5 Stage Preload Adjuster, Steel Hollow Cross Swingarm

Engine

Tank Capacity (l)	17,5 (Incl Reserve)
Fuel System	PGM-Fuel Injection
Oil Capacity (l)	3,2l
Fuel Consumption (WMTC)	3,6l/100km / 27,8km/l
Engine Configuration	Liquid-cooled, 4-stroke DOHC Parallel Twin
Displacement (cm ³)	471cc
Cylinders	2
Valves Per Cylinder	4
Bore x Stroke (mm)	67mm x 66.8mm
Compression Ratio	10.7 : 1
Power (kW)	35kW @ 8600rpm
Torque (Nm)	43Nm @ 6500rpm

Electrical System

Starter	Electric
Battery Capacity	12V 7,4AH



All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

**NX**
500**Honda NX500**

Safety

ABS System Type	2 Channel
Front Brakes	Dual 296mm x 4mm Disc with Nissin Axial mounted two piston callipers
Rear Brakes	Single 240mm x 5mm Disc with Nissin single piston calliper
Emergency Stop Signal (ESS)	Yes

Drive Train

Drive	Chain
Clutch Type	Wet Multiple, assisted slipper clutch
Transmission Type	6-speed

Styling

Frame Material	Steel Diamond
----------------	---------------

Instruments & Electronics

Instruments	5-inch TFT Meter with customisable layout, including but not limited to: Speedometer, Tachometer, Clock, Gear Position, Shift Up Indicator
Security System	HISS (Honda Intelligent Security System)
Headlight	LED
Taillight	LED
Connectivity	Yes (Honda RoadSync)

Wheels

Type Front	Multi-spoke cast aluminium
Type Rear	Multi-spoke cast aluminium
Rim Size Front	19M/C x MT2.5
Rim Size Rear	17M/C x MT4.5
Tyres (f)	110/80R19M/C59H
Tyres (r)	160/60R17M/C69H

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.