

**TRANSALP**

25ym Honda XL750 Transalp

General

Warranty	2 yrs / Unlimited Km
Service Intervals	12 000kms

Dimensions & Weights

Claimed KERB Weight (kg)	210 kgs
Length (mm)	2 325 mm
Width (mm)	838 mm
Height (mm)	1 455 mm
Seat Height (mm)	850 mm
Wheel Base (mm)	1 560 mm
Ground Clearance (mm)	210 mm
Turning Radius (m)	2,6 m
Caster Angle (degrees)	27°
Trail (mm)	111 mm

Suspension

Front Suspension	Showa 43 mm SFF-CA USD, 200 mm travel
Rear Suspension	Monoshock damper, Prolink swingarm, 190 mm travel

Engine

Tank Capacity (l)	16.9 l
Fuel System	PGM-FI
Oil Capacity (l)	3,9l
Fuel Consumption	4.3 L/100km
Engine Configuration	Liquid-cooled OHC 4-stroke 8-valve Parallel Twin with 270° crank and uni-cam
Displacement (cm ³)	755cc
Cylinders	2
Valves Per Cylinder	4
Bore x Stroke (mm)	87mm x 63,5mm
Compression Ratio	11.0 : 1
Power (kW)	67,5kW @ 9 500rpm
Torque (Nm)	75Nm @ 7 250rpm
CO ² Emissions (WMTC)	102 g/km
Stationary Sound Level (dB)	95 dB
Max Speed	195 km/h

Styling

Frame Type	Diamond Steel Frame
------------	---------------------



All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.

**TRANSALP**

25ym Honda XL750 Transalp

Safety

ABS System Type	Dual-channel ABS (Rear ABS can be deactivated)
Front Brakes	Axial mounted two-piston brake caliper, 310 mm floating double disc
Rear Brakes	Single piston caliper, 256 mm single disc

Drive Train

Final Drive	Chain
Clutch Type	Wet Multiple, assisted slipper clutch
Transmission Type	6-speed Manual Transmission

Wheels

Wheels	Stainless spoke, Aluminium rim, Tube type
Tyres (f)	90/90-21M/C 54H
Tyres (r)	150/70R18M/C 70H

Instruments & Electronics

Instruments	Five-inch TFT Panel Multi information display
Security System	HISS (Honda Intelligent Security System)
Headlight	LED
Taillight	LED
Connectivity	Honda RoadSync
USB	Type C
Auto winker cancel	Yes
Riding Modes	Sport, Standard, Rain, Gravel and User Mode
HSTC	Three Levels + OFF
Additional Features	ESS

Electrical System

Starter	Electric
Battery Type	AGM
Battery Capacity	12 V 9.1 Ah



All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.