



24ym Honda TRX420FA6

General

Warranty	6 months
Service Intervals	As per User Manual

Dimensions & Weights

Claimed KERB Weight (kg)	312 kg
Length (mm)	2 146 mm
Width (mm)	1 204 mm
Height (mm)	1 199 mm
Seat Height (mm)	899 mm
Wheel Base (mm)	1 295 mm
Ground Clearance (mm)	243 mm
Towing Capacity	384 kg
Payload Capacity	30 Kg. F / 60Kg. R
Turning Radius (m)	3.5 m
Fuel Capacity	14 Ltr., incl. 5 Ltr. reserve

Suspension

Type Front	Independent double-wishbone; 185mm. travel
Type Rear	Independent double-wishbone; 216mm. travel

Engine

Type	420cc liquid-cooled OHV wet-sump longitudinally mounted single-cylinder four-stroke
Valve Train	OHV pushrod & rocker arm; 2 valves/cylinder
Bore x Stroke (mm)	86.5 mm x 71.5 mm
Compression Ratio	9.9:1
Induction	Programmed Fuel Injection (PGM-FI), 34mm throttle body
Ignition	Full transistorized with electronic advance
Starter	Electric
Driveline	F/R driveshaft w/ TraxLok® and torque-sensing front differential
Transmission	Automatic ESP push-button; 5-speed + Reverse
Clutch	Automatic

Safety

Front Brakes	Dual hydraulic calipers w/ 190mm discs
Rear Brakes	Single hydraulic caliper w/ 170mm disc

Wheels

Tyres Front	24 x 8-12
Tyres Rear	24 x 10-11

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.