



## 24ym Honda TRX420FA6 TRX420 TM1

### General

Warranty	6 months
Service Intervals	As per User Manual

### Dimensions & Weights

	TRX420FA6	TRX420TM1
Claimed KERB Weight (kg)	312 kg	263 kg
Length (mm)	2 146 mm	2 103 mm
Width (mm)	1 204 mm	1 204 mm
Height (mm)	1 199 mm	1 173 mm
Seat Height (mm)	899 mm	856 mm
Wheel Base (mm)	1 295 mm	1 270 mm
Ground Clearance (mm)	243 mm	180 mm
Towing Capacity	384 kg	384 kg
Payload Capacity	30 kg Front 60kg Rear	30 kg Front 60kg Rear
Turning Radius (m)	3.5 m	2.8 m
Fuel Capacity	14 litre, incl. 5 litre reserve	

### Engine

	TRX420FA6	TRX420TM1
Driveline	F/R driveshaft w/ TraxLok® and torque-sensing front differential	Direct rear driveshaft; two-wheel drive
Transmission	Automatic DCT ESP push-button; 5-speed + Reverse	Foot Shift, 5-speed Manual + Reverse
Type	420cc liquid-cooled OHV wet-sump longitudinally mounted single-cylinder four-stroke	
Valve Train	OHV pushrod & rocker arm; 2 valves/cylinder	
Bore x Stroke (mm)	86.5 mm x 71.5 mm	
Compression Ratio	9.9:1	
Induction	Programmed Fuel Injection (PGM-FI), 34mm throttle body	
Ignition	Full transistorized with electronic advance	
Starter	Electric	
Clutch	Automatic	

### Wheels

	TRX420FA6	TRX420TM1
Tyres Front	24 x 8-12	24 x 8-12
Tyres Rear	24 x 10-11	24 x 10-11

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.





## 24ym Honda TRX420FA6 TRX420 TM1

### Suspension

	TRX420FA6	TRX420TM1
Type Front	Independent double-wishbone; 185mm. travel	Independent double-wishbone; 170mm. travel
Type Rear	Independent double-wishbone; 216mm. travel	Swingarm w/ single shock; 170mm. travel

### Styling

	TRX420FA6	TRX420TM1
Colours	Hero Red	Hero Red

### Brakes

	TRX420FA6	TRX420TM1
Front	Dual hydraulic calipers with 190mm discs	Dual hydraulic calipers with 190mm discs
Rear	Independent double-wishbone; 216mm. travel	Single 160mm sealed mechanical drum