



Honda CBR1000RR-R SP

General

Warranty	2 yrs / Unlimited Km
Service Intervals	12 000kms

Dimensions & Weights

Claimed KERB Weight (kg)	201 kgs
Length (mm)	2 105 mm
Width (mm)	750 mm
Height (mm)	1 140 mm
Seat Height (mm)	830 mm
Wheel Base (mm)	1 455 mm
Trail (mm)	101,9 mm
Caster Angle (degrees)	24,7

Safety

ABS System Type	2 Channel
Front Brakes	330mm disc with radial-mount 4-piston Brembo Stylema R caliper
Rear Brakes	220mm disc with 2-piston Brembo caliper
Emergency Stop Signals (ESS)	Yes

Engine

Tank Capacity (l)	16,5l
Fuel System	PGM-FI
CO ² Emissions	155g/km
Fuel Consumption	14,9km/L (6,7l/100km)
Engine Configuration	Liquid-cooled 4-stroke 16-valve DOHC Inline-4
Displacement (cm ³)	1000cc
Cylinders	4
Valves Per Cylinder	4
Bore x Stroke (mm)	81mm x 48,5mm
Compression Ratio	13.6:1
Max Power (kW)	160kW @ 14,000
Max Torque (Nm)	113Nm @ 12,000
Oil Capacity (l)	4
Noise Level	Lurban 76.2dB, LWOT 81.1dB

Electrical System

Starter	Electric
Battery Capacity	12-2.3Ah HJ12L (Li-ion)

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.



Honda CBR1000RR-R SP

Suspension

Front Suspension	Öhlins 43mm S-EC3.0 (Spool Valve) NPX USD Forks, with preload, compression & rebound adjustments, 125mm stroke.
Rear Suspension	Öhlins TTX36 S-EC3.0 (Spool Valve) Pro-Link Swing Arm with preload, compression and rebound damping, 143mm stroke.

Drive Train

Drive	Chain
Clutch Type	Wet, Multiple clutch
Transmission Type	Manual 6-speed

Styling

Frame Material	Aluminium twin tube composite twin spar
----------------	---

Instruments & Electronics

Instruments	5" TFT
Security System	HISS / Honda Smart Key (Keyless Start)
Headlight	LED
Taillight	LED
Auto Winker Cancel	Yes
Quickshifter	Yes
Additional Feature	2 Motor TBW

Wheels

Front Rim Size	17" x MT3.5
Rear Rim Size	17" x MT6.0
Tyres (f)	120/70-ZR17 M/C (58W)
Tyres (r)	200/55-ZR17 M/C (78W)

All specifications are provisional and subject to change without notice. Please note that the figures provided are results obtained by Honda under standardised testing conditions prescribed by WMTC. Tests are conducted on a rolling road using a standard version of the vehicle with only one rider and no additional optional equipment. Actual fuel consumption may vary depending on how you ride, how you maintain your vehicle, weather, road conditions, tire pressure, installation of accessories, cargo, rider and passenger weight, and other factors.