

Africa Twin



CRF1100L ADVENTURE SPORT

MT & DCT Versions available



Honda DCT
Dual Clutch Transmission



Engine Type

OHC liquid-cooled
4-stroke 8-valve
parallel twin with 270°
crank and Uni-cam



Max. Torque

112Nm @
5,500rpm



Starter

Electric



Fuel Tank Capacity

24.8 Litres



Kerb Weight

MT: 243kg
DCT: 253kg



Seat Height

835/855mm
(Low seat option 795mm)



SCAN TO
START YOUR
ADVENTURE

Recommended Retail Price (MT)

R324,749

Price subject to change



ENGINE

Type	Liquid-cooled OHC 4-stroke 8-valve Parallel Twin with 270° crank and Uni-cam
Displacement	1084cc
Bore x Stroke	92 mm x 81.5 mm
Compression Ratio	10.5:1
Max. Power Output	75kW at 7,500rpm
Max. Torque	112Nm at 5,500rpm
Oil Capacity	MT: 4.8 L • DCT: 5.2 L

FUEL SYSTEM

Carburation	PGM-FI
Fuel Tank Capacity	24.8 L
CO2 Emissions	114g/km
Fuel Consumption	20.5 km/L - 4.9 L/100km

ELECTRICAL SYSTEM

Battery Capacity	12V-6Ah Li-ion BATTERY (20Hr)
------------------	-------------------------------

DRIVETRAIN

Clutch Type	MT: Wet, multiplate with coil springs, Aluminium Cam Assist and Slipper clutch • DCT: 2 wet, multiplate clutches with coil springs
Transmission Type	MT: 6-speed Manual • DCT: 6-speed DCT
Final Drive	O-ring sealed chain

FRAME

Type	Semi Double Cradle
------	--------------------

CHASSIS

Dimensions (L*W*H)	2,305mm x 960mm x 1,475mm
Wheelbase	1,570mm
Caster Angle	27.5°
Trail	106mm

CHASSIS

Seat Height	835/855mm (Low Seat option 795mm)
Ground Clearance	220mm
Kerb Weight	MT: 243kg • DCT: 253kg

SUSPENSION

Type Front	SHOWA Telescopic inverted fork with an inner tube diameter of 45mm, and an electronic control unit (SHOWA EERATM) with compression and rebound damping adjustments, 210mm stroke
Type Rear	Monoblock aluminium swing arm with Pro-Link with SHOWA gas-charged damper, hydraulic remote control preload adjuster and electronic control unit (SHOWA EERATM) with compression and rebound damping adjustments, 200 mm rear wheel travel.

WHEELS

Type Front	19M/C x MT2.50 wire spoke with aluminium rim
Type Rear	18M/C x MT4.00 wire spoke with aluminium rim
Tyres Front	110/80-R19M/C 59V (Tubeless type) Bridgestone Battlax Adventure A41
Tyres Rear	150/70-R18M/C 70H (Tubeless type) Bridgestone Battlax Adventure A41

BRAKES

ABS System Type	2 channel with IMU - Selectable ABS MODE with ON road and OFF road setting
Type Front	310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers and sintered metal pads
Type Rear	256mm wave hydraulic disc with single piston caliper and sintered metal pads.

INSTRUMENTS & ELECTRONICS

Instruments	LCD Meter, TFT 6.5" touch panel multi information display
Headlight / Taillight	LED / LED

AFTER SALES

Warranty	2 yrs / Unlimited Km
Service intervals	12 000km