

Africa Twin



CRF1100L AFRICA TWIN

MT & DCT Versions available



Honda DCT
Dual Clutch Transmission



Engine Type

Liquid-cooled OHC
4-stroke 8-valve
Parallel Twin with 270°
crank and Uni-cam



Max. Torque

112Nm @
5,500rpm



Transmission

6-Speed
Manual & DCT



Fuel Tank Capacity

18.8 Litres



Kerb Weight

MT: 231kg
DCT: 242kg



Seat Height

850/870 mm
(Low seat: 825mm
Comfort seat: 885mm)



SCAN TO
START YOUR
ADVENTURE

Recommended Retail Price (MT)

R279,399

Price subject to change



ENGINE

Type	Liquid-cooled OHC 4-stroke 8-valve Parallel Twin with 270° crank and Uni-cam
Displacement	1084cc
Bore x Stroke	92 mm x 81.5 mm
Compression Ratio	10.5:1
Max. Power Output	75kW at 7,500rpm
Max. Torque	112Nm at 5,500rpm
Oil Capacity	MT: 4.8 L • DCT: 5.2 L

FUEL SYSTEM

Carburation	PGM-FI
Fuel Tank Capacity	18.8 L
CO2 Emissions	114g/km
Fuel Consumption	20.5 km/L - 4.9 L/100km

ELECTRICAL SYSTEM

Battery Capacity	12V-6Ah Li-ion BATTERY (20Hr)
------------------	-------------------------------

DRIVETRAIN

Clutch Type	MT: Wet, multiplate with coil springs, Aluminium Cam Assist and Slipper clutch • DCT: 2 wet, multiplate clutches with coil springs
Transmission Type	MT: 6-speed Manual • DCT: 6-speed DCT
Final Drive	O-ring sealed chain

FRAME

Type	Semi Double Cradle
------	--------------------

CHASSIS

Dimensions (L*W*H)	2,330mm x 960mm x 1,485mm
Wheelbase	1,575mm
Caster Angle	27.5°
Trail	113mm

CHASSIS

Seat Height	850/870mm (Low Seat option 825, Comfort Seat option 885)
Ground Clearance	250mm
Kerb Weight	MT: 231kg • DCT: 242kg

SUSPENSION

Type Front	Showa 45mm cartridge-type inverted telescopic fork with dial-style preload adjuster and DF adjustments, 230mm stroke.
Type Rear	Monoblock aluminium swing arm with Pro-Link with SHOWA gas-charged damper, hydraulic dial-style preload adjuster and rebound damping adjustments, 220 mm rear wheel travel.

WHEELS

Type Front	21M/C x MT2.15 wire spoke with aluminium rim
Type Rear	18M/C x MT4.00 wire spoke with aluminium rim
Tyres Front	90/90-21M/C 54H (tubeless type) Metzler Karoo Street)
Tyres Rear	150/70R18M/C 70H (tubeless type) Metzler Karoo Street)

BRAKES

ABS System Type	2 channel with IMU - Selectable ABS MODE with ON road and OFF road setting
Type Front	310mm dual wave floating hydraulic disc with aluminium hub and radial fit 4-piston calipers and sintered metal pads
Type Rear	256mm wave hydraulic disc with single piston caliper and sintered metal pads.

INSTRUMENTS & ELECTRONICS

Instruments	LCD Meter, TFT 6.5" touch panel multi information display
Headlight / Taillight	LED / LED
Connectivity	Bluetooth and Apple CarPlay® / Android Auto® (wired)
USB / 12V Socket	Yes / Yes
Quickshifter	Optional (MT only)
Riding Modes	Tour, Urban, Gravel, Off-Road and 2 User Modes

AFTER SALES

Warranty	2 yrs / Unlimited Km
Service intervals	12 000km