

NX 500

NX500

MT & E-Clutch Versions available

Honda E-Clutch



Engine Type

2 Cylinders, Liquid-cooled 4-stroke DOHC parallel twin



Max. Torque

**43Nm @
6,500rpm**



Starter

E-Starter



Fuel Tank Capacity

17.5 Litres



Kerb Weight

**MT: 196kg
E-Clutch: 199kg**



Seat Height

830mm



**SCAN TO
START YOUR
ADVENTURE**

Recommended Retail Price (E-Clutch)

R141,399

Price subject to change



ENGINE

Type	2 Cylinders, Liquid-cooled 4-stroke DOHC parallel twin
Displacement	471 cc
Bore x Stroke	67 mm x 66.8 mm
Compression Ratio	10.7:1
Max. Power Output	35 kw (47hp) at 8,500 rpm
Max. Torque	43 Nm at 6,500 rpm
Noise Level	90
Oil Capacity	3.1 L

FUEL SYSTEM

Carburation	PGM FI electronic fuel injection
Fuel Tank Capacity	17.5L
CO2 Emissions	82 g/km
Fuel Consumption	3.6 L/100km

ELECTRICAL SYSTEM

Battery	AGM 12 V 7.4 Ah
Starter	E-Starter

DRIVETRAIN

Clutch Type	MT: Wet multiplate, Assisted slipper clutch E-Clutch: Wet multiplate, Assisted slipper clutch
Transmission Type	6-speed
Final Drive	Chain

FRAME

Type	Steel diamond
------	---------------

CHASSIS

Dimensions (L*W*H)	2,165 mm x 830 mm x 1,415 mm
Wheelbase	1,445 mm

CHASSIS

Caster Angle	27.5°
Trail	108 mm
Seat Height	830 mm
Ground Clearance	180 mm
Kerb Weight	MT: 196 kg • E-Clutch: 199 kg
Turning Radius	2.4 m

SUSPENSION

Type Front	Showa 41 mm SFF-BP USD forks
Type Rear	Prolink mono with 5 stage preload adjuster, steel hollow cross swingarm

WHEELS

Type Front	19M/C X MT2.5 5Y-Spoke Cast Aluminium
Type Rear	17M/C X MT4.5 5Y-Spoke Cast Aluminium
Tyres Front	110/80R19M/C (59H)
Tyres Rear	160/60R17M/C (69H)

BRAKES

ABS System Type	2-channel
Type Front	Dual 296 mm x 4 mm disc with Nissin axial mounted two piston calipers
Type Rear	Single 240 mm x 5 mm disc with single piston caliper

INSTRUMENTS & ELECTRONICS

Instruments	5-inch TFT Meter with customisable layout
Headlight / Taillight	LED / LED
Connectivity	Honda RoadSync
Security System	HISS
Additional Features	ESS

AFTER SALES

Warranty	2 yrs / Unlimited Km
Service intervals	1st service 1000 km thereafter every 12000 km