

NX 500

NX500

MT & E-Clutch Versions available*

Honda E-Clutch



Engine Type
Liquid-cooled,
4-stroke DOHC
parallel twin



Max. Torque
43Nm @
6,500rpm



Starter
Electric



**Fuel Tank
Capacity**
17.5 Litres
(inc. reserve)



Kerb Weight
MT: 196kg
E-Clutch:
199kg



Seat Height
830mm

HONDA



SCAN TO
START YOUR
ADVENTURE

*While Stocks Last

ENGINE

Type	Liquid-cooled 4-strokeDOHC parallel twin
Displacement	471 cc
Bore x Stroke	67 mm x 66.8 mm
Compression Ratio	10.7:1
Max. Power Output	35 kw (47hp) at 8,500 rpm
Max. Torque	43 Nm at 6,500 rpm
Noise Level	90
Oil Capacity	3.1 L

FUEL SYSTEM

Carburation	PGM FI electronicfuelinjection
Fuel Tank Capacity	17.5L
CO2 Emissions	82 g/km
Fuel Consumption	3.6 L/100km

ELECTRICAL SYSTEM

Battery Capacity	12 V 7.4Ah
-------------------------	------------

DRIVETRAIN

Clutch Type	Wet multiplate, Assisted slipper clutch E-Clutch: Wet multiplate, Assisted slipper clutch
Transmission Type	6-speed
Final Drive	Chain

FRAME

Type	Steel diamond
-------------	---------------

CHASSIS

Dimensions (L*W*H)	2,165 mm x830mmx1,415 mm
Wheelbase	1,445 mm
Caster Angle	27.5°
Trail	108 mm
Seat Height	830 mm
Ground Clearance	180 mm
Kerb Weight	196 kg • E-Clutch: 199 kg

SUSPENSION

Type Front	Showa 41 mm SFF-BP USD forks
Type Rear	Prolink mono with 5 stage preload adjuster, steel hollow cross swingarm

WHEELS

Type Front	19M/C X MT2.5 5Y-Spoke Cast Aluminium
Type Rear	17M/C X MT4.5 5Y-Spoke Cast Aluminium
Tyres Front	110/80R19M/C (59H)
Tyres Rear	160/60R17M/C (69H)

BRAKES

ABS System Type	2-channel
Type Front	Dual 296 mm x 4 mm disc with Nissin axial mounted two piston calipers
Type Rear	Single 240 mm x 5 mm disc with single piston caliper

AFTER SALES

Warranty	2 yrs / Unlimited Km
Service intervals	12 000km

