

TRANSALP

 **HONDA**

XL750 TRANSALP

MT & E-Clutch Versions available

Honda E-Clutch



Engine Type
Liquid-cooled
SOHC 4-stroke
8-valve Parallel Twin
with 270° crank



Max. Torque
75Nm @
7,250rpm



Transmission
Manual &
E-Clutch



Fuel Tank Capacity
15.2 Litres



Kerb Weight
210kg
E-Clutch: 216kg



Seat Height
850mm



SCAN TO
START YOUR
ADVENTURE




HONDA

ENGINE

Type	Liquid-cooled SOHC4-stroke 8-valve Parallel Twin with 270° crank and uni-cam
Displacement	755 cc
Bore x Stroke	87 mm x 63.5 mm
Compression Ratio	11.0:1
Max. Power Output	67.5 kW at 9,500 rpm
Max. Torque	75 Nm at 7,250 rpm
Noise Level	95 dB
Oil Capacity	3.9 L

FUEL SYSTEM

Carburation	PGM-FI
Fuel Tank Capacity	16.9 L
CO2 Emissions	102 g/km
Fuel Consumption	4.3 L/100km

ELECTRICAL SYSTEM

Battery Capacity	12 V 9.1Ah
-------------------------	------------

DRIVETRAIN

Clutch Type	Wet multiple, Assisted slipper clutch
Transmission Type	6-speed Manual Transmission & E-Clutch
Final Drive	Chain

FRAME

Type	Diamond Steel Frame
-------------	---------------------

CHASSIS

Dimensions (L'W'H)	2,325 mm x 838mm x 1,455 mm
Wheelbase	1,560 mm
Caster Angle	27°
Trail	111 mm
Seat Height	850 mm
Ground Clearance	210 mm
Kerb Weight	MT: 210 kg • E-Clutch: 216 kg

SUSPENSION

Type Front	Showa 43mm SFF-CAUSD, 200 mm travel
Type Rear	Monoshock damper, Prolink swingarm, 190 mm travel

WHEELS

Type Front	Stainless spoke, Aluminium rim, Tube type
Type Rear	Stainless spoke, Aluminium rim, Tube type
Tyres Front	90/90-21M/C 54H
Tyres Rear	150/70R18M/C 70H

BRAKES

ABS System Type	Dual-channel ABS (Rear ABS can be deactivated)
Type Front	Axial mounted two-piston brake caliper, 310 mm floating double disc
Type Rear	Single piston caliper, 256 mm single disc

AFTER SALES

Warranty	2 yrs / Unlimited Km
Service intervals	1 st Service at 1000km ; thereafter every 12 000km